



SKYLIGHT CURB DETAIL
NOT TO SCALE

NOTE:

SLOPED ROOFS REQUIRE HORIZONTAL LEG OF FLASHING TO BE INSTALLED OVER ROOFING MATERIAL AT BOTTOM, UNDERNEATH ROOFING MATERIAL ON TOP & SIDES.

INNOVATIVE BUILDING PRODUCTS, INC. ASSUMES NO RESPONSIBILITY FOR THE DESIGN, CONSTRUCTION OR FABRICATION OF THE SUPPORTING STRUCTURE. DESIGN OF SUCH IS THE SOLE RESPONSIBILITY OF THE PROJECT ENGINEER/ARCHITECT. INNOVATIVE BUILDING PRODUCTS, INC. IS ONLY RESPONSIBLE FOR THE ENGINEERING AND STRUCTURAL INTEGRITY OF THE ALUMINUM GRID SYSTEM ITSELF.

THE SUPPORTING STRUCTURE MUST BE DESIGNED TO SUPPORT:
DESIGN LIVE LOAD = 20 psf
DESIGN DEAD LOAD = 15 psf (ACTUAL SELF WEIGHT INCLUDING GLASS BLOCK)
ANY ADDITIONAL LOADS REQUIRED BY THE GOVERNING BUILDING CODES

Innovative Building Products, Inc.
P.O. Box 425 Fort Worth, TX 76101
Phone: (800) 932-2263
Fax: (817) 332-1406
Plant: 206 Dotson St. Denton, TX 76205

GlassWalk™
IBP GLASS FLOOR SYSTEMS

**FAST TRACK
STONE** system™

IBP
glass block grid system™

SK-1

JAN. 2017