



## WINDOW (FLUSHMOUNT) AS CANOPY

NOT TO SCALE

ALL STEEL SURFACES THAT COME INTO CONTACT WITH THE ALUMINUM GRID SYSTEM SHOULD BE PAINTED WITH RED OXIDE PRIMER (OR EQUIVALENT) TO ENSURE AGAINST ELECTROLYSIS.

**NOTE:**  
 INNOVATIVE BUILDING PRODUCTS, INC. ASSUMES NO RESPONSIBILITY FOR THE DESIGN, CONSTRUCTION OR FABRICATION OF THE SUPPORTING AND/OR CONTAINMENT OPENING. DESIGN OF SUCH IS THE SOLE RESPONSIBILITY OF THE PROJECT ENGINEER / ARCHITECT. INNOVATIVE BUILDING PRODUCTS, INC. IS ONLY RESPONSIBLE FOR THE ENGINEERING AND STRUCTURAL INTEGRITY OF THE FLOOR GRID SYSTEM ITSELF.

### THE SUPPORTING STRUCTURE MUST BE DESIGNED TO SUPPORT:

DESIGN SNOW LOAD = 25 PSF

DESIGN DEAD LOAD = 20 PSF (ACTUAL SELF WEIGHT INCLUDING GLASS BLOCK)

ANY ADDITIONAL LOADS REQUIRED BY THE GOVERNING BUILDING CODES.

Because IBP has no control over installation, workmanship, accessory materials or conditions of application, no representation or warranty, expressed or implied, either as to MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE is made as to the performance or results of an installation of this product.

Innovative Building Products, Inc.  
 P.O. Box 425 Fort Worth, TX 76101  
 Phone: (800) 932-2263  
 Fax: (817) 332-1406  
 Plant: 206 Dotson St. Denton, TX 76205

**GlassWalk™**  
 IBP GLASS FLOOR SYSTEMS

**FAST TRACK  
 STONE** system™

**IBP**  
 glass block grid system™

**CPY-1**

JAN. 2017